



### GENERATOR SET

WATER COOLED THREE PHASES 50 HZ DIESEL

|             |         |         |
|-------------|---------|---------|
| Standby     | kVA     | 66      |
|             | kW      | 52,80   |
| Prime       | kVA     | 60      |
|             | kW      | 48,00   |
| Motor Devri | r.p.m   | 1500    |
| Voltaj      | V       | 230/400 |
| Güç Faktörü | Cos Phi | 0,8     |

### CERTIFICATIONS

GUCBIR Company with quality certification ISO 9001

GUCBIR gensets are compliant with EC mark which includes the following directives:

- 2006/42/EC Machinery safety.
- 2014/30/EU Electromagnetic compatibility.
- 2014/35/EU Electrical equipment designed for use within certain voltage limits
- 2000/14/EC Sound Power level. Noise emissions outdoor equipment. (amended by 2005/88/EC)
- 97/68/EC Emissions of gaseous and particulate pollutants. (amended by 2002/88/EC & 2004/26/EC)
- EN 12100, EN 13857, EN 60204

Ambient conditions of reference according to ISO 8528-1:2005 normative: 1000 mbar, 25°C, 30% relative humidity.

G2 class load acceptance in accordance with ISO 8528-5:2013





## Engine



## Alternator

### Engine

### Specifications


|                                             |       |                                |
|---------------------------------------------|-------|--------------------------------|
| Gross Engine Output                         | kWm   | 81,4 / 73,3                    |
| Manufacturer                                |       | HD Hyundai ( Old name Doosan ) |
| Model                                       |       | SP344CC                        |
| Engine Type                                 |       | 4 Stroke - Diesel              |
| Injection Type                              |       | Direct Injection               |
| Aspiration Type                             |       | Turbocharged                   |
| Number of cylinder                          |       | 4                              |
| Bore and Stroke                             | mm    | 98 x 113                       |
| Displacement                                | L     | 3,4                            |
| Cooling System                              |       | Water Cooling                  |
| Fuel Consumption 50% PRP                    | l/h   | 9.4                            |
| Fuel Consumption 75% PRP                    | l/h   | 13.6                           |
| Fuel Consumption 100 % PRP                  | l/h   | 18.1                           |
| Fuel Consumption Standby                    | l/h   | -                              |
| Oil fuel consumption ratio                  | %fuel | ≤0.1%                          |
| Total oil capacity including tubes, filters | L     | 6 ~ 12.6 L                     |
| Total coolant capacity                      | L     | 14.2 L (Engine only: 4 L)      |
| Electric system voltage(V)                  | V     | 12                             |

### Alternator

### Specifications

|                                 |      |                     |
|---------------------------------|------|---------------------|
| Manufacturer                    |      | Leroy Somer         |
| Model                           |      | TAL-A44-C/TAL-044-C |
| Output Voltage                  | V    | 230/400             |
| Frequency                       | HZ   | 50                  |
| Automatic Voltage Regulation    | ±%   | 1                   |
| Alternator Standby Power        | kVA  | 66                  |
| Alternator Continuous Power     | kVA  | 60                  |
| Power Factor                    | Cosφ | 0,8                 |
| Number of Wires                 |      | 12                  |
| Winding                         |      | 2/3                 |
| Protection Class                |      | IP23 / H            |
| Excitation System               |      | Self Excited        |
| AVR Model                       |      | R120                |
| Performance - PF 0,8 / %75 Load | %    | 90                  |

## DIMENSIONS



## CANOPIED

|           |    |                |
|-----------|----|----------------|
| LxWxH     | mm | 2980x1100x2089 |
| Weight    | kg | 1360           |
| Fuel Tank | lt | 500            |

### Sound Proof Canopy

- Special design for minimizing acoustic level.
- Galvanized steel construction further protected by polyester powder coat paint.
- Black finish stainless steel locks and hinges.
- Control panel viewing window in a lockable access door.
- Emergency stop push button (red) mounted on enclosure exterior.
- Lifting, drag and jacking points on base frame.
- Radiator fill via removable, flush mounted rain cap fitted with compression seal.
- Acoustic insulation with moisture-repellent and non-flammable material

### CONTROL UNIT



Control Unit

#### DATAKOM D-500-MK3

|                                      |                                |
|--------------------------------------|--------------------------------|
| ATS unit with uninterrupted transfer | Internet Central Monitoring    |
| AMF unit with uninterrupted transfer | SMS / E-mail message sending   |
| Remote / Manuel start controller     | Flexible with plug-in modules  |
| Engine controller                    | Free PC software: Rainbow Plus |
| GSM-GPRS-GPS-Ethernet Port           | Modbus RTU                     |
| 8 configurable digital inputs        |                                |

### ATS PANEL

GUCBIR automatic transfer switches are reliable, rugged, versatile, and compact assemblies for transferring essential loads and electrical distribution systems from one power source to another. GUCBIR's contactor, changeover and MCCB based transfer switch is rated 40-3600A and can be supplied in separate enclosures for standalone applications or can be supplied as an integral component contactors, changeovers and MCCB's, inside the ATS panels are well known and internationally recognized brands such as ABB, SIEMENS, SCHNEIDER, GE, LS, HYUNDAI and ANDELI.



### OPTIONAL EQUIPMENTS

Some Optional Equipments that GUCBIR provides with Generator Sets;

- Medium voltage alternator,
- Remote radiator applications,
- Automatic fuel filling system,
- Fuel tank, oil pan, dashboard, alternator, coil heaters,
- Alternator with double AVR and PMG,
- Synchronization systems, The generator output breaker,
- Grid-generator transfer switches,
- Accordance with the specific volume of demand-insulated cabins,
- Seismic solutions,
- Trailer,
- Remote monitoring.
- SMPS 12/24V 10A

